

# Steel Electric Powered Tugger 2000 Lb. Pull Capacity Yellow/Black

**MODEL E-TUG-20**

Industrial Carts & Dollies / Electric Powered Tuggers



## PRODUCT OVERVIEW

The electric powered Tuggers are ideal for industrial facilities, hospitals, airports, and wholesale/retail stores. The unit is designed of a durable construction for constantly strong use on a daily basis. Tugger is perfect for confined areas due to its short turning radius. An infinite throttle position allows for unlimited forward and reverse adjustments for precise positioning. Unit can be tilted forward manually to align the hitch if needed. An integral battery charger and level gauge allow for convenient as needed charging and level awareness. Pin hitch standard, optional attachments available.

## KEY FEATURES

- Ergonomic handle for easy operation while diminishing the need of bending and twisting
- Dead-man activation for the utmost safety and security
- Forward and reverse operations for precise maneuverability
- High torque for heavy duty operations

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**235 lbs**

**ASSEMBLED SIZE**  
**27.5" W x 38.5" L x 53.125" H**

**SHIP WEIGHT**  
**282 lbs**

**PACKAGE 1 SIZE**  
**42" W x 48" D x 58" H**

**COLOR / FINISH**  
**Black & Yellow**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                 |                                                                            |
|---------------------------------|----------------------------------------------------------------------------|
| Uniform Pull Capacity (lbs.)    | 2,000                                                                      |
| Drive Motor                     | 24V DC                                                                     |
| Battery Qty./Volts              | (2) 12V                                                                    |
| Horsepower (HP)                 | 1                                                                          |
| Handle Height (in.)             | 53-1/8                                                                     |
| Wheel Qty./Size (in.)           | (2) 12-1/4 x 4-3/4                                                         |
| Wheel Material                  | Solid Foam                                                                 |
| Caster Qty./Size (in.)          | (3) 4 x 1-1/4                                                              |
| Caster Material                 | Polyurethane                                                               |
| Loaded Speed (MPH)              | 2.3                                                                        |
| Unloaded Speed (MPH)            | 2.7                                                                        |
| Pull Motor (KW)                 | 0.8                                                                        |
| Maximum Gradeability (degrees)  | 2                                                                          |
| Unloaded Gradeability (degrees) | 3                                                                          |
| Battery Depth                   | 7.76                                                                       |
| Battery Width                   | 5.125                                                                      |
| Battery Height                  | 7.125                                                                      |
| Battery Weight                  | 21.67                                                                      |
| Battery Freight Class           | 70                                                                         |
| Battery NMFC Number             | 60680                                                                      |
| Battery NMFC Description        | Batteries or Cells, Offered for transportation as a Hazard Class 4, 8 or 9 |
| Battery Subclass                | 1                                                                          |
| Lithium Battery Configuration   | C -- Contained In                                                          |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1019>